

KOLD KATCHER

INCORPORATED

HEAT TRACING SYSTEMS

Solar Pump Skid

Industrial Solar Pumping Systems

www.koldkatcher.com



ENVIRONMENTALLY SOUND

Eliminates on-site vent gas associated with gas driven pumps venting to atmosphere

ECONOMICAL

Eliminates daily operating costs associated with conventional circulating systems
Easily converted to on-site AC/DC remote power system

DESIGN RATING

Designed for remote locations with heat trace or other circulating requirements
750' 1/2" S.S. Tubing Maximum Loop Distance

PRODUCTIVITY

Available pump rates include:
0.75 gal/min
2.5 to 8.0 gal/min

DEPENDABILITY

High Efficiency, Low Voltage Circulating Pump
Control technology ensures optimum efficiency

RELIABILITY

Extended service life

APPLICATIONS

Glycol Heat Tracing
Glycol circulation
Water pumping
Cooling Systems

Ideal for remote locations and installations. Industrial applications where performance, endurance and reliability are a must.

**Actual product may not appear exactly as shown.*

See reverse for performance specifications and ordering information

Model: Solar Pump Skid

Specifications	
Module Capacity	280 – 420 Watts Standard (Expandable)
Battery Amp Hours	660 – 990 Amp Hours
Battery Warmer	Integral
High Efficiency, Low Voltage Circulating Pump (S.S)	12 or 24 volt available
Weather Proof Vented Insulated Enclosure	Standard
Skid Mount	Standard
Secondary Containment	Integral
Design Pressure	100 psi – 640 kpa
Trace Line Capacity	750'
Fittings	Stainless steel
Weight	Various
Skid Dimensions	Various



Size: SPS 280



Size: SPS 560

- The Solar Pumping Skid eliminates on-site vent gas associated with gas driven pumps
- Eliminates daily operating costs associated with conventional circulating systems
- Remote circulating system designed for extreme environments
- Available in various sizes